

不锈钢外球面轴承

型号	d	D	Bi	Be	r	N	M	G	ds	Cr (KN)	Cor (KN)	重量 (Kg)
SB201	12	40	22.0	12	1.0	6.0	16.0	4.5	M5*0.8	7.82	3.58	0.10
SB201-8	12.7	40	22.0	12	1.0	6.0	16.0	4.5	M5*0.8	7.82	3.58	0.10
SB202	15	40	22.0	12	1.0	6.0	16.0	4.5	M5*0.8	7.82	3.58	0.09
SB202-10	15.875	40	22.0	12	1.0	6.0	16.0	4.5	M5*0.8	7.82	3.58	0.09
SB203	17	40	22.0	12	1.0	6.0	16.0	4.5	M5*0.8	7.82	3.58	0.08
SB203-11	17.463	40	22.0	12	1.0	6.0	16.0	4.5	M5*0.8	7.82	3.58	0.08
SB204	20	47	25.0	14	1.5	7.0	18.0	4.5	M6*0.75	10.37	5.04	0.12
SB204-12	19.05	47	25.0	14	1.5	7.0	18.0	4.5	M6*0.75	10.37	5.04	0.13
SB205	25	52	27.0	15	1.5	7.5	19.5	5.0	M6*0.75	11.31	5.97	0.17
SB205-14	22.225	52	27.0	15	1.5	7.5	19.5	5.0	M6*0.75	11.31	5.97	0.18
SB205-15	23.813	52	27.0	15	1.5	7.5	19.5	5.0	M6*0.75	11.31	5.97	0.17
SB205-16	25.4	52	27.0	15	1.5	7.5	19.5	5.0	M6*0.75	11.31	5.97	0.16
SB206	30	62	30.0	16	1.5	8.0	22.0	5.5	M6*0.75	15.73	8.64	0.25
SB206-17	26.988	62	30.0	16	1.5	8.0	22.0	5.5	M8*1.0	15.73	8.64	0.28
SB206-18	28.575	62	30.0	16	1.5	8.0	22.0	5.5	M8*1.0	15.73	8.64	0.26
SB206-19	30.163	62	30.0	16	1.5	8.0	22.0	5.5	M8*1.0	15.73	8.64	0.25
SB206-20	31.75	62	30.0	16	1.5	8.0	22.0	5.5	M8*1.0	15.73	8.64	0.23
SB207	35	72	32.0	17	2.0	8.5	23.5	6.0	M8*1.0	20.83	11.68	0.37
SB207-20	31.75	72	32.0	17	2.0	8.5	23.5	6.0	M8*1.0	20.83	11.68	0.41
SB207-21	33.338	72	32.0	17	2.0	8.5	23.5	6.0	M8*1.0	20.83	11.68	0.39
SB207-22	34.925	72	32.0	17	2.0	8.5	23.5	6.0	M8*1.0	20.83	11.68	0.37
SB207-23	36.513	72	32.0	17	2.0	8.5	23.5	6.0	M8*1.0	20.83	11.68	0.35
SB208	40	80	34.0	18	2.0	9.0	25.0	8.0	M8*1.0	23.55	13.60	0.45
SB208-24	38.1	80	34.0	18	2.0	9.0	25.0	8.0	M8*1.0	23.55	13.60	0.48
SB208-25	39.688	80	34.0	18	2.0	9.0	25.0	8.0	M8*1.0	23.55	13.60	0.45
SB209	45	85	41.2	19	2.0	10.2	31.0	8.0	M8*1.0	26.44	19.56	0.80
SB209-26	41.275	85	41.2	19	2.0	10.2	31.0	8.0	M8*1.0	26.44	19.56	0.80
SB209-27	42.863	85	41.2	19	2.0	10.2	31.0	8.0	M8*1.0	26.44	19.56	0.80
SB209-28	44.45	85	41.2	19	2.0	10.2	31.0	8.0	M8*1.0	26.44	19.56	0.80
SB210	50	90	43.5	20	2.0	10.9	32.6	9.0	M8*1.0	30.01	22.53	0.87
SB210-29	46.038	90	43.5	20	2.0	10.9	32.6	9.0	M8*1.0	30.01	22.53	0.87
SB210-30	47.625	90	43.5	20	2.0	10.9	32.6	9.0	M8*1.0	30.01	22.53	0.87
SB210-31	49.213	90	43.5	20	2.0	10.9	32.6	9.0	M8*1.0	30.01	22.53	0.87
SB210-32	50.8	90	43.5	20	2.0	10.9	32.6	9.0	M8*1.0	30.01	22.53	0.87
SB211	55	100	45.3	21	2.5	11.8	33.5	10.0	M8*1.0	32.29	24.00	1.10
SB211-32	50.8	100	45.3	21	2.5	11.8	33.5	10.0	M10*1.25	32.29	24.00	1.10
SB211-33	52.388	100	45.3	21	2.5	11.8	33.5	10.0	M10*1.25	32.29	24.00	1.10
SB211-34	53.975	100	45.3	21	2.5	11.8	33.5	10.0	M10*1.25	32.29	24.00	1.10
SB211-35	55.563	100	45.3	21	2.5	11.8	33.5	10.0	M10*1.25	32.29	24.00	1.10
SB212	60	110	53.7	22	2.5	14.9	38.8	10.0	M10*1.25	35.28	26.18	1.30
SB212-36	57.15	110	53.7	22	2.5	14.9	38.8	10.0	M10*1.25	35.28	26.18	1.30
SB212-37	58.738	110	53.7	22	2.5	14.9	38.8	10.0	M10*1.25	35.28	26.18	1.30
SB212-38	60.325	110	53.7	22	2.5	14.9	38.8	10.0	M10*1.25	35.28	26.18	1.30
SB212-39	61.913	110	53.7	22	2.5	14.9	38.8	10.0	M10*1.25	35.28	26.18	1.30

不锈钢外球面轴承

型号	d	D	Bi	Be	r	N	M	G	ds	T	Cr (KN)	Cor (KN)	重量 (Kg)
SUC201	12	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.21
SUC201-8	12.7	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.20
SUC202	15	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.19
SUC202-9	14.288	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.19
SUC202-10	15.875	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.19
SUC203	17	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.18
SUC203-11	17.463	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.18
SUC204	20	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.16
SUC204-12	19.05	47	31	17	1.0	12.7	18.3	4.7	M6*0.75	4.0	10.37	5.08	0.16
SUC205	25	52	34.1	17	1.5	14.3	19.8	5	M6*0.75	4.2	11.31	6.00	0.19
SUC205-14	22.225	52	34.1	17	1.5	14.3	19.8	5	M6*0.75	4.2	11.31	6.00	0.22
SUC205-15	23.813	52	34.1	17	1.5	14.3	19.8	5	M6*0.75	4.2	11.31	6.00	0.20
SUC205-16	25.4	52	34.1	17	1.5	14.3	19.8	5	M6*0.75	4.2	11.31	6.00	0.19
SUC206	30	62	38.1	19	1.5	15.9	22.2	5	M6*0.75	5.0	15.81	8.64	0.31
SUC206-17	26.988	62	38.1	19	1.5	15.9	22.2	5	M6*0.75	5.0	15.81	8.64	0.36
SUC206-18	28.575	62	38.1	19	1.5	15.9	22.2	5	M6*0.75	5.0	15.81	8.64	0.34
SUC206-19	30.163	62	38.1	19	1.5	15.9	22.2	5	M6*0.75	5.0	15.81	8.64	0.32
SUC206-20	31.75	62	38.1	19	1.5	15.9	22.2	5	M6*0.75	5.0	15.81	8.64	0.31
SUC207	35	72	42.9	20	2.0	17.5	25.4	6	M8*1.0	5.7	20.83	11.68	0.46
SUC207-20	31.75	72	42.9	20	2.0	17.5	25.4	6	M8*1.0	5.7	20.83	11.68	0.52
SUC207-21	33.338	72	42.9	20	2.0	17.5	25.4	6	M8*1.0	5.7	20.83	11.68	0.50
SUC207-22	34.925	72	42.9	20	2.0	17.5	25.4	6	M8*1.0	5.7	20.83	11.68	0.48
SUC207-23	36.513	72	42.9	20	2.0	17.5	25.4	6	M8*1.0	5.7	20.83	11.68	0.46
SUC208	40	80	49.2	21	2.0	19	30.2	8	M8*1.0	6.3	23.55	13.60	0.63
SUC208-24	38.1	80	49.2	21	2.0	19	30.2	8	M8*1.0	6.3	23.55	13.60	0.68
SUC208-25	39.688	80	49.2	21	2.0	19	30.2	8	M8*1.0	6.3	23.55	13.60	0.64
SUC209	45	85	49.2	22	2.0	19	30.2	8	M8*1.0	6.3	26.35	15.60	0.70
SUC209-26	41.275	85	49.2	22	2.0	19	30.2	8	M8*1.0	6.3	26.35	15.60	0.78
SUC209-27	42.863	85	49.2	22	2.0	19	30.2	8	M8*1.0	6.3	26.35	15.60	0.74
SUC209-28	44.45	85	49.2	22	2.0	19	30.2	8	M8*1.0	6.3	26.35	15.60	0.70
SUC210	50	90	51.6	24	2.0	19	32.6	10	M10*1.25	6.6	28.48	18.00	0.78
SUC210-29	46.038	90	51.6	24	2.0	19	32.6	10	M10*1.25	6.6	28.48	18.00	0.89
SUC210-30	47.625	90	51.6	24	2.0	19	32.6	10	M10*1.25	6.6	28.48	18.00	0.85
SUC210-31	49.213	90	51.6	24	2.0	19	32.6	10	M10*1.25	6.6	28.48	18.00	0.80
SUC210-32	50.8	90	51.6	24	2.0	19	32.6	10	M10*1.25	6.6	28.48	18.00	0.78
SUC211	55	100	55.6	25	2.5	22.2	33.4	10	M10*1.25	7.0	35.28	22.40	1.07
SUC211-32	50.8	100	55.6	25	2.5	22.2	33.4	10	M10*1.25	7.0	35.28	22.40	1.22
SUC211-33	52.388	100	55.6	25	2.5	22.2	33.4	10	M10*1.25	7.0	35.28	22.40	1.18
SUC211-34	53.975	100	55.6	25	2.5	22.2	33.4	10	M10*1.25	7.0	35.28	22.40	1.10
SUC211-35	55.563	100	55.6	25	2.5	22.2	33.4	10	M10*1.25	7.0	35.28	22.40	1.05
SUC212	60	110	65.1	27	2.5	25.4	39.7	10	M10*1.25	7.6	42.50	26.34	1.52
SUC212-36	57.15	110	65.1	27	2.5	25.4	39.7	10	M10*1.25	7.6	42.50	26.34	1.65
SUC212-37	58.738	110	65.1	27	2.5	25.4	39.7	10	M10*1.25	7.6	42.50	26.34	1.55
SUC212-38	60.325	110	65.1	27	2.5	25.4	39.7	10	M10*1.25	7.6	42.50	26.34	1.49
SUC212-39	61.913	110	65.1	27	2.5	25.4	39.7	10	M10*1.25	7.6	42.50	26.34	1.42
SUC213	65	120	65.1	28	2.5	25.4	39.7	10	M10*1.25	8.9	46.50	30.40	1.80
SUC213-40	63.5	120	65.1	28	2.5	25.4	39.7	10	M10*1.25	8.9	46.50	30.40	1.88
SUC213-41	65.088	120	65.1	28	2.5	25.4	39.7	10	M10*1.25	8.9	46.50	30.40	1.80
SUC214	70	125	74.6	30	2.5	30.2	44.4	12	M12*1.5	8.9	50.15	33.60	2.06
SUC214-42	66.675	125	74.6	30	2.5	30.2	44.4	12	M12*1.5	8.9	50.15	33.60	2.10
SUC214-43	68.263	125	74.6	30	2.5	30.2	44.4	12	M12*1.5	8.9	50.15	33.60	2.08
SUC214-44	69.85	125	74.6	30	2.5	30.2	44.4	12</					